

environments such as meat or fish processing plants,

dairies, pharmaceutical and chemical industry.

Ø74x93

Ø74x70

Item/Type ACZ20H ACZ20L Capacity Q 2000 2000 Min. fork height h 75 mm 85 Max. fork height h 200 190 Steering wheel Ø200x50 Ø180x50

160x60

520/540/685

1100/1150/1220

Ø80x93

Ø80x70

mm

mm

mm

Fork length I

Conforms to EN 1757-2

Load roller Single

Load roller Tandem

Width overall forks B

Size of fork e*s

GALVANIZED PALLET TRUCK

 All the exposed parts of the whole truck galvanized, including hydraulic pump, fork frame, handle and so on.

 Special application in cold and wet environments resists the effects of cold, condensation and washing.

 Nylon steering wheel and fork rollers as standard option for damp or harsh environments applications.

 With pressure relief valve and overload valve to prevent pump damages when loads exceed weight limits.

 The one-piece pump design simplifies repairs, assuring reliable service and long life.

STAINLESS PALLET TRUCK

Stainless pallet truck		1KG=2.2LB 1INCH=25.4MM	
Item/Type		ACS20H	ACS20L
Capacity Q	kg	2000	2000
Min. fork height h	mm	85	75
Max. fork height h₁	mm	200	190
Steering wheel	mm	Ø200x50	Ø180x50
Load roller Single	mm	Ø80x93	Ø74x93
Load roller Tandem	mm	Ø74X70	Ø74x70
Size of fork e*s	mm	160x60	
Width overall forks B	mm	520/540/685	
Fork length I	mm	1000/1100/1150/1220	

Conforms to EN 1757-2

- All metal parts made completely stainless steel, including hydraulic pump, fork frame, handle and so on.
- Ideal transport aid for application in damp or harsh environments such as meat or fish
 processing plants, dairies, pharmaceutical and chemical industry.
- With pressure relief valve and overload valve to prevent pump damages when loads exceeds weight limits.
- The enclosed fork tips (for Aisi316 stainless truck only) ensure there is no dead corner where corrosive spatters remains and damages the truck.
- Specially designed for applications where hygiene is of utmost importance.
- Nylon steering wheel and fork rollers as standard option for damp or harsh environments applications.

