

PS16DN

The range of stacker includes the wide list of models with capacity from 1200kg to 2000kg and lifting height up to 5500mm.


INTRODUCTION

The truck designed to be used with high efficiency even during their multi-shift operation. The configuration of the truck allows you to get more powerful and productive units thanks to its increased speed and different options of batteries, including Lithium solutions.

ADVANTAGES:

- The new model range of short-tiller trucks introduced by Noblift has combined all the experience gained by the manufacturer over past years. By using of the most advanced solutions and top level components, the new range is ready to provide the top level of performance to its users.
- During the design stage, several priorities and various details were considered and verified such as improvement of the service life and performance of our trucks, easy maintenance as well as confirmation of interchangeability of components not only within model range, but also with other ranges of Noblift products.
- The experience of Noblift shows that the use of top brand components from well-known suppliers not only helps to improve reliability, but also gain trust from our customers and put the products to a new level. That is why nearly all key components used for the model range are coming from famous brands with rich experience in material handling industry.





Powerful AC-drive unit from the global industry leaders: the AC driving motor designed and produced by Schabmuller comes together with the top quality ZF gearbox and it is equipped with Intorq electromagnetic brake. The drive unit can provide the drive speed up to 8 km/h. The use of top level quality drive wheels from German manufacturers Rader Vogel or Wicke helps to ensure the long life time of PU tires.



The integrated design of operator's platform and protective arms as well as totally new internal structure allows to ensure the smallest body length of the stackers and provide extremely low turning radius among competitors. Together with this, the suspension system for the platform helps to provide the high level of comfort to operators.



The use of apron with 8 mm thickness allows to ensure the robustness of chassis and its strength even in case of collision against objects. The strong battery cover made out of steel helps to provide a high level of strength for this part.



Rema tiller delivers high level of ergonomics as well as reliability of control system. In addition, the tiller ensures a long life-time thanks to the contactless rocker switches designed for lifting/lowering function .




The driving controllers and steering controllers are manufactured by Zapi (Italy) - the leading European brand with long history in the industry, which provides extremely reliable and flexible solutions with high performance level of the control system.



The option of PIN-code panel access, which works not only with PIN-code but also with access cards (RFID) , can significantly simplify the procedure of access limitation for the fleet which may be used by more than one operator.





PS16DN



The model range can be equipped with the option of Electric Power Steering (EPS) which delivers precise and fast control for the position of steering wheel and has a high level of reliability as well as safety according to official standards.

Mast table PS16DN

Designation	Lowered mast height h1(mm)	Free lift height h2(mm)	Lift height h3(mm)	Extended mast height h4(mm)	Lift+fork height h3+h13(mm)
PS16DN					
Two stage mast	1955	/	2830	3380	2920
	2105	/	3130	3680	3220
	2305	/	3530	4080	3620
Two stage mast FFL (Full-Free-Lift)	1955	1410	2830	3380	2920
	2105	1560	3130	3680	3220
	2305	1760	3530	4080	3620
Three stage mast	2005	/	4230	4780	4300
	2105	/	4530	5080	4600
Three stage mast FFL (Full-Free-Lift)	1905	1320	3930	4480	4000
	2005	1420	4230	4780	4300
	2105	1520	4530	5080	4600



Type sheet for industrial truck acc. to VDI 2198 1KG=2.2LB 1INCH=25.4MM

Identification

1.2	Manufacturer's type designation		PS16DN(4600)
1.3	Drive		Battery
1.4	Operator type		Pedestrian
1.5	Load Capacity / rated load		1.6
	Load capacity at mast lift	Q (t)	1.6
	Load capacity at support arm lift		1.6
1.6	Load centre distance	c (mm)	600
1.8	Load distance ,centre of drive axle to fork	x (mm)	767 ¹⁾
1.9	Wheelbase	y (mm)	1480 ²⁾

Weights

2.1	Service weight	kg	1390
2.2	Axle load at full load, drive side/load side	kg	1096/1854
2.3	Axle load at no load, drive side/load side	kg	920/430

Wheels\ Chassis

3.1	Tires		Polyurethane (PU)
3.2	Tire size,front	Øx w (mm)	Φ230×70
3.3	Tire size,rear	Øx w (mm)	Φ84×70
3.4	Additional wheels(dimensions)	Øx w (mm)	Φ150×54
3.5	Wheels,number front/rear(x=driven wheels)		1x+1/4
3.6	Tread, front	b10 (mm)	504
3.7	Tread, rear	b11 (mm)	390/505

Basic Dimensions

4.2	Lowered mast height	h1(mm)	2105
4.3	Free Lift height	h2(mm)	1520
4.4	Lift	h3(mm)	4530
4.5	Extended maximal height	h4(mm)	5080
4.6	Initial lift	h5(mm)	120
4.9	Height of tiller in drive position min./ max.	h14 (mm)	900/1350
4.15	Height, lowered	h13 (mm)	90
4.19	Overall length	l1 (mm)	2044 ¹⁾
4.20	Length to face of forks	l2 (mm)	894 ¹⁾
4.21	Overall width	b1 (mm)	790
4.22	Fork dimensions	s/e/l (mm)	60/180/1150
4.25	Width across forks	b5 (mm)	570/685
4.32	Ground clearance, centre of wheelbase	m2 (mm)	20
4.33	Aisle width for pallets1000X1200 crossways	Ast (mm)	2586 ²⁾
4.34	Aisle width for pallets800X1200 lengthways	Ast (mm)	2566 ²⁾
4.35	Turning radius	Wa (mm)	1700 ²⁾

Performance Data

5.1	Travel speed, laden/ unladen	km/h	6.0/7.0
5.2	Lift speed, laden/ unladen	m/s	0.09/0.14
5.3	Lowering speed, laden/ unladen	m/s	0.25/0.20
5.8	Max. gradeability, laden/ unladen	%	6/12
5.10	Service brake		Electromagnetic

E-Motor

6.1	Drive motor rating S2 60min	kW	1.4
6.2	Lift motor rating at S3 10%	kW	3.2
6.3	Battery acc. to DIN 43531/ 35/ 36 A, B, C, no		3VBS
6.4	Battery voltage, nominal capacity K5	V / Ah	24/270
6.5	Battery weight	kg	230
6.6	Energy consumption acc. to VDI cycle	kWh/h	0.73

Other Details

8.1	Type of drive control		AC- speed control
8.4	Sound level at driver's ear acc. to EN 12053	dB(A)	<70

1) when operate the fork and pallet at the same time: Load Capacity / rated load (mast lift) < Load Capacity / rated load (support arm lift)

2) Load section lowered: -74mmmm